


Flowcoat UCR



Description

Flowcoat UCR is a two pack, solvent free, novolac epoxy resin based coating with extremely high chemical resistance.


Uses

To provide a light to medium duty, easy to clean, extremely high chemical resistant floor coating. A non-slip finish can be produced by the incorporation of aggregates between coats. Typical uses are processing, manufacturing, packaging and chemical storage areas subject to heavy foot and pallet truck traffic.

Benefits

- Extremely high chemical resistance
- High abrasion resistance
- Solvent free and low odour
- Attractive, light reflective appearance
- Seamless and hygienic finish
- Low maintenance
- Slip resistant finish can be tailored to specific client requirements


Standard Colour Chart



Ivory




Yellow



Light Blue



Dark Blue



Light Green




Dark Green




Brick Red



Light Grey




Steel Grey



Charcoal

System Design



Model Specification

Product: Flowcoat UCR
Finish: Gloss
Thickness: Dependant on specification
Colour: _____
Preparatory work and application in accordance with suppliers instructions.
Manufacturer: Flowcrete Middle East FZCO
Telephone : Customer Service +971 4 886 4728

Substrate Requirements

Concrete or screed substrate should be a minimum of 25N/ mm², free from laitance, dust and other contamination. The substrate should be dry to 75% RH as per BS8204 and free from rising damp and ground water pressure.

Products Included in this System

Flowcoat UCR

Detailed application instructions are available upon request.

Installation Service

The installation should be carried out by a Flowcrete approved applicator with a documented quality assurance scheme. Obtain details of our approved contractors by contacting our customer service team or enquiring via our website at www.flowcrete.ae

Environmental Considerations

The finished system is assessed as non-hazardous to health and the environment. The long service life and seamless surface reduce the need for repairs, maintenance and cleaning. Environmental and health considerations are controlled during the manufacture and application of the products by Flowcrete staff and fully trained and experienced contractors.

Focus on the Floorzone

Flowcrete Middle East FZCO is a division of the Flowcrete Group, world leaders in specialist industrial and commercial flooring. Systems available include: underfloor heating systems, floor screeds, surface damp proof membranes, decorative floor finishes, seamless terrazzo, car park deck waterproofing and corrosion protection systems... to name just a few. Our corporate objective is to satisfy your flooring needs.

Technical Information

The figures that follow are typical properties achieved in laboratory tests at 20°C and at 50% Relative Humidity.

Fire Resistance	BS476: Part 7: Surface spread of flame: Class 1
Slip Resistance	TRRL Pendulum Slip Test Dry >40, Wet depends on specification

Textured systems are recommended to meet slip resistance value requirements for wet conditions and/or surface contaminants (wet or dry) - please contact our Technical Advisors for further details and specifications.

Thermal Resistance	Tolerant up to 70°C
Water Permeability	Nil – Karsten test (impermeable)
Surface Hardness	180 secs.Koenig Hardness Test
Chemical Resistance	Contact Technical Department
Abrasion Resistance	Taber Abrader: 80mg loss per 1000 cycles (1kg load using CS10 wheels)
Compressive Strength	> 60 N/mm ² (BS6319)
Flexural Strength	> 40 N/mm ² (BS6319)
Tensile Strength	> 15 N/mm ² (BS6319)
Bond Strength	Greater than cohesive strength of 25 N/mm ² concrete. >1.5 MPa.

Speed of Cure

	10°C	20°C	30°C
Light Traffic	48 hrs	24 hrs	18 hrs
Full traffic	72 hrs	48 hrs	36 hrs
Full chemical cure	12 days	7 days	6 days

Aftercare - Cleaning and Maintenance

Clean regularly using a single or double headed rotary scrubber drier in conjunction with a mildly alkaline detergent.

Important Note

Flowcrete's products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and Conditions of Sale, copies of which can be obtained on request.

Further Information

To ensure you are specifying a fit for purpose flooring for your project please consult our Technical Advisors on the number below or visit our website to register your interest in specifying one of the most durable floors on the market.